



220-240V AC, Phasenanschnitt LED- Netzgerät 24V 50-120W IP67 dimmbar

Article nr.: 85490

rutec dimmable LED power supply, constant voltage · for indoor and outdoor use · Protection class I, CE, REACH, RoHS, SELV, active PFC · Protection against short circuit, overload, over voltage and over temperature · Primary and secondary sided 1 input and output line · Housing: aluminium · Input voltage: 220-240V AC · Power: 50-120 watt · output current: 2.08-5.0 A · output voltage: 24 Volt · LxWxH in mm: 250 x 80.3 x 33.5 · temperature range: -20 to +50°C · dimmable on primary side via TRIAC dimmer · dimming range: 3-100%

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094854908
Housing colour	Aluminium
Length	250.00 mm
Width	80.30 mm
Height	33.50 mm
Lamp	without
IP rating	67
Power	50-120 W
Psb	0,00 W






220-240V AC, Phasenanschnitt LED- Netzgerät 24V 50-120W IP67 dimmbar

Article nr.: 85490

TECHNICAL DATA

P _{no}	0,85 W
Current mA	2.083-5.000 mA
Input voltage	220-240
Output voltage	24
Material	Aluminium
Tolerance	5.00
Temperature range	-20 - 50
Suitable light source	LED





**220-240V AC, Phasenanschnitt LED-
Netzgerät 24V 50-120W IP67 dimmbar**
Article nr.: 85490

TECHNICAL DRAWING

