





220V-240V 50/60Hz CRI80 LARA AC RUND Eisengeb. 6W IP44


Article nr.: LED54205WW-V2

for indoor use, IP 44 · · housing: die-cast aluminum, glass frosted · housing color: brushed iron · not swivelling · beam angle: 95° · power: 6 W · light colour: 3000 K · luminous flux: 519 lm · CRI: >80 · lifespan L70B50: >= 50.000 h · input: 230 V AC · protection class I, MM · · installation depth: 28 mm · installation diameter: 55 mm · outer diameter: 82 mm · energy efficiency class: F · not dimmable · When used in alternating or cross connection, an LED compensator must be used in · parallel with the switching wire

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094042053
Housing colour	Eisen-gebürstet
Height	24.00 mm
Outer diameter	82 mm
Hole size	55 mm
Depth in ceiling	28.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	519.00 lm
Lamp	including LED







220V-240V 50/60Hz CRI80 LARA AC
RUND Eisengeb. 6W IP44
Article nr.: LED54205WW-V2

TECHNICAL DATA

IP rating	44
Furniture downlight	1
Power	6 W
Psb	0,00 W
Current mA	26 mA
Voltage	230 V
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 50
Energy efficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	50.000 h
Suitable light source	





220V-240V 50/60Hz CRI80 LARA AC
RUND Eisengeb. 6W IP44

Article nr.: LED54205WW-V2

TECHNICAL DRAWING

