



weiss, RGBWW QILE - 23, 55W IP43
110° 350mA
Article nr.: 45101

RGBW LED recessed downlight with diffuse lighting surface · for indoor use. IP43 · · housing: diecast aluminum, plastic diffuser white · housing color: white · not swivelling · beam angle: 110° · power: 23.55 W (white 6.5 W) · light color: 3000K + RGB · luminous flux: 966 lm · luminous flux 3000K: 560 lm · CRI: >80 · lifetime: L70B50: >= 50.000 h · Input current: 350 mA DC · · Installation depth: 96 mm · Ceiling cut-out: 105 mm · Outer diameter: 121 mm · Energie efficiency class: G · not including LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094451015
Housing colour	Weiss
Outer diameter	121 mm
Hole size	105 mm
Depth in ceiling	96.00 mm
LED colour	RGBW 3000K
Lightoutput per fixture	966.00 lm
Lightoutput per LED	26.83 lm
Lamp	including LED





weiss, RGBWW QILE - 23, 55W IP43

110° 350mA

Article nr.: 45101

TECHNICAL DATA

IP rating	43
Power	23,55 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	36
Material	Aluminium
Temperature range	-20 - 40
Energy efficiency class	EEK-Label_G
CRI	≥ 80
Lifetime L70B50	50.000 h
Suitable light source	

