



## TALU LED-Einbaustrahler ohne Konverter schwenk., rund, 350mA, 8W, IP20, 4000K, CRI90-Weiß matt

Article nr.: ALU57341NWOK-M

for indoor use, IP20 · housing: diecast aluminium, glass reflector, protective glass · housing color: white matt · 30° swiveling · beam angle: 40° · power: 8 W · light color: 4,000 K · luminous flux: 735 lm · CRI: >90 · lifetime L70B50: >= 54,000 h · input: 350 mA · protection class III · installation depth: 40 mm · ceiling cut-out: 68 mm · outer diameter: 82 mm · energie efficiency class: F · not included LED converter

### TECHNICAL DATA

|                         |                       |
|-------------------------|-----------------------|
| Unit Code               | pcs                   |
| BAR code                | 4012094672410         |
| Housing colour          | Weiss matt            |
| Height                  | 31.00 mm              |
| Outer diameter          | 82 mm                 |
| Hole size               | 68 mm                 |
| Depth in ceiling        | 40.00 mm              |
| LED colour              | ca. 4000K neutralweiß |
| Lightoutput per fixture | 735.00 lm             |
| Lamp                    | including LED         |





**TALU LED-Einbaustrahler ohne Konverter  
schwenk., rund, 350mA, 8W, IP20,  
4000K, CRI90-Weiß matt**

Article nr.: ALU57341NWOK-M

## TECHNICAL DATA

|                         |             |
|-------------------------|-------------|
| IP rating               | 20          |
| Power                   | 8 W         |
| Psb                     | 0,00 W      |
| Current mA              | 350 mA      |
| Lamp base               | ohne        |
| Material                | Aluminium   |
| Temperature range       | -20 - 40    |
| Energy efficiency class | EEK-Label_F |
| CRI                     | ≥ 90        |
| Lifetime L70B50         | 54.000 h    |
| Suitable light source   |             |





**TALU LED-Einbaustrahler ohne Konverter**  
**schwenk., rund, 350mA, 8W, IP20,**  
**4000K, CRI90-Weiß matt**  
Article nr.: ALU57341NWOK-M

#### TECHNICAL DRAWING

