



TALU LED-Einbaustrahler 1er Set
dimmbar Plug&play schwenk., rund,
350mA, 8W, IP20, 2700K, CRI90 -Eisen
geb

Article nr.: ALU57345UWWD-V2

for indoor use, IP20 · · housing: diecast aluminium, glass reflector, protective glass · housing colour: brushed iron · 30° swiveling · beam angle: 40° · power: 8 W · light colour: 2700 K · luminous flux: 694 lm · CRI: >90 · lifespan L70B50: >= 54,000 h · input voltage range: 220-240 V AC, 50/60 Hz · protection class II · · installation depth: 40 mm · ceiling cut out: 68 mm · outer diameter: 82 mm · including constant current converter dimmable via TRIAC dimmer · with connector for plug-and-play-operation · tool-free replacement of the lamp · this product contains a light source of energy efficiency class F

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094643458
Housing colour	Weiss
Height	31.00 mm
Outer diameter	82 mm
Hole size	68 mm
Depth in ceiling	40.00 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	694.00 lm
Lamp	including LED





TALU LED-Einbaustrahler 1er Set dimmbar Plug&play schwenk., rund, 350mA, 8W, IP20, 2700K, CRI90 -Eisen geb

Article nr.: ALU57345UWWD-V2

TECHNICAL DATA

IP rating	20
Power	8 W
Psb	0,00 W
Current mA	350 mA
Lamp base	sonstige
Input voltage	220-240
Material	Aluminium
Temperature range	-20 - 45
CRI	≥ 90
Lifetime L70B50	54.000 h
Suitable light source	





TALU LED-Einbaustrahler 1er Set
dimmbar Plug&play schwenk., rund,
350mA, 8W, IP20, 2700K, CRI90 -Eisen
geb

Article nr.: ALU57345UWWD-V2

TECHNICAL DRAWING

