



**TALU LED-Einbaustrahler ohne
Konverter schwenk., rund, 350mA, 8W,
IP20, 2700K, CRI90 -Eisen geb**
Article nr.: ALU57345UWWOK

for indoor use, IP20 · housing: diecast aluminium, glass reflector, protective glass · housing color: brushed iron · 30° swiveling · beam angle: 40° · power: 8 W · light color: 2.700 K · luminous flux: 694 lm · CRI: >90 · lifetime L70B50: >= 54.000 h · input: 350 mA DC · protection class III · installation depth: 40 mm · ceiling cut-out: 68 mm · outer diameter: 82 mm · energie efficiency class: F · not included LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094073453
Housing colour	Eisen-gebürstet
Outer diameter	82 mm
Hole size	68 mm
Depth in ceiling	40.00 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	694.00 lm
Lamp	including LED
IP rating	20





**TALU LED-Einbaustrahler ohne
Konverter schwenk., rund, 350mA, 8W,
IP20, 2700K, CRI90 -Eisen geb**
Article nr.: ALU57345UWWOK

TECHNICAL DATA

Power	8 W
Current mA	350 mA
Lamp base	ohne
Material	Aluminium
Temperature range	-20 - 45
Energy efficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	54.000 h
Suitable light source	

