



**TALU LED-Einbaustrahler ohne
Konverter schwenk., rund, 350mA, 8W,
IP20, 3000K, CRI90 -Eisen geb**
Article nr.: ALU57345WWOK

for indoor use, IP20 · housing: diecast aluminium, glass reflector, protective glass · housing color: brushed iron · 30° swiveling · beam angle: 40° · power: 8 W · light color: 3.000 K · luminous flux: 715 lm · CRI: >90 · lifetime L70B50: >= 54.000 h · input: 350 mA DC · protection class III · installation depth: 40 mm · ceiling cut-out: 68 mm · outer diameter: 82 mm · energie efficiency class: F · not included LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094473451
Housing colour	Eisen-gebürstet
Outer diameter	82 mm
Hole size	68 mm
Depth in ceiling	40.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	715.00 lm
Lamp	including LED
IP rating	20





**TALU LED-Einbaustrahler ohne
Konverter schwenk., rund, 350mA, 8W,
IP20, 3000K, CRI90 -Eisen geb**
Article nr.: ALU57345WWOK

TECHNICAL DATA

Power	8 W
Current mA	350 mA
Lamp base	ohne
Material	Aluminium
Temperature range	-20 - 45
Energy efficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	54.000 h
Suitable light source	

