




2000-2800K 40° 350mA CRI80
m.Scheibe LED Einbaustr. 7W
altmessing o.Konv.


Article nr.: ALU57356DTWOK

for indoor use, IP 20 · housing: diecast aluminum, glass reflector, protective glass · housing color: old brass · 30° swivelling · beam angle: 40° · power: 7 W · light color: 2200 - 2800 K DimToWarm · luminous flux: 580 lm · CRI: >80 · lifetime L70B50: >= 50.000 h · input: 350 mA DC · protection class III · installation depth: 40 mm · ceiling cut-out: 68 mm · outer diameter: 82 mm · energie efficiency class: F · not included LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094071565
Housing colour	Altmessing
Height	34.00 mm
Outer diameter	82 mm
Hole size	68 mm
Depth in ceiling	40.00 mm
LED colour	2800-2000K Dim to Warm
Lightoutput per fixture	580.00 lm
Lamp	including LED





2000-2800K 40° 350mA CRI80

m.Scheibe LED Einbaustr. 7W


altmessing o.Konv.

Article nr.: ALU57356DTWOK

TECHNICAL DATA

IP rating	20
Power	7 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
Energy efficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	50.000 h
Suitable light source	





2000-2800K 40° 350mA CRI80
m.Scheibe LED Einbaustr. 7W
altmessing o.Konv.

Article nr.: ALU57356DTWOK

TECHNICAL DRAWING

