



VARDAflex Eco AC 4000K Flex.LED-Strip, 200-240V 50/60Hz IP65

Article nr.: S74928-V2

for outdoor use, IP65 and UV resistant · can be separated every 500 mm or 27 LEDs · number of LEDs per meter: 54 · LED pitch: 18.51 mm · beam angle: 120° · CRI: >90 · lumen per meter: 633 lm · voltage: 230V AC · power per meter: 8 W · lifetime L70B50: >= 30.000 h · energy efficiency class: G · WxH in mm: 15,5 x 6.5 · Easy installation with solderless connector. · Maximum length per connection: 50 meter. New connectors for greater length.

TECHNICAL DATA

Unit Code	metre
BAR code	4012094741284
Housing colour	Weiss
Width	15.50 mm
Height	6.50 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per LED	11.72 lm
Lamp	including LED
IP rating	65
Voltage	220-240 V





VARDAflex Eco AC 4000K Flex.LED-Strip, 200-240V 50/60Hz IP65
Article nr.: S74928-V2

TECHNICAL DATA

Material	Kunststoff
Temperature range	-20 - 40
LED per meter	54
Dimension of segments	500.00 mm
Energy efficiency class	EEK-Label_G
CRI	≥ 90
Lifetime L70B50	30.000 h
Suitable light source	

