



VARDAflex AC Eco 4000K Flex.LED-Strip, 200-240V 50/60Hz IP65

Article nr.: S74928

for outdoor use, IP65 · UV resistant · can be separated every 50 cm or 27 LEDs · number of LEDs: 54 · LED pitch: 18.51 mm · beam angle: 120° · CRI: >90 · lumen per meter: 519 lm · voltage: 230V AC · power per meter: 8 W · lifetime L70B50: >= 30.000 h · energy efficiency class: G · WxH in mm: 15,5 x 6 · Easy installation with solderless connector. · Maximum length per connection: 50 meter. New connectors for greater length.

TECHNICAL DATA

Unit Code	metre
BAR code	4012094049281
Housing colour	Weiss
Length	1000.00 mm
Width	15.50 mm
Height	6.00 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per LED	9.62 lm
Lamp	including LED
IP rating	65





VARDAflex AC Eco 4000K Flex.LED-Strip, 200-240V 50/60Hz IP65
Article nr.: S74928

TECHNICAL DATA

Voltage	220-240 V
Input voltage	230
Temperature range	-20 - 40
LED per meter	54
Dimension of segments	500.00 mm
Energy efficiency class	EEK-Label_G
CRI	≥ 90
Lifetime L70B50	30.000 h
Suitable light source	

