




VARDaflex Standard IP67 Reach25 Flex.LED Strip, 24V, IP67, 3000K

Article nr.: 86550-V2

flexible LED-strip with self adhesive backside, · for indoor and outdoor use, IP67 · not uv-resistant · ·
can be separated every 100 mm or 6 LEDs · number of LEDs: 1500 · LED pitch: 16.67 mm · beam
angle: 120° · CRI: >80 · luminous flux per meter: 385 lm · input: 24V DC · power per meter: 3.6 W ·
lifetime L70B50: >= 50,000 h · energy efficiency class: E · LxWxH in mm: 25,000 x 12 x 6 · · Maximum
length per connection: 25 meter. New connectors for greater length. · Delivery contents: 5 meter reel
with 150 mm connecting cable, · 100 x mounting bracket made from silicone, 4 x in-feeder cap, · 4x
end cap

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094265506
Length	25000.00 mm
Width	12.00 mm
Height	6.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	9625.00 lm
Lightoutput per LED	6.42 lm
Lamp	including LED
IP rating	67






VARDaflex Standard IP67 Reach25
Flex.LED Strip, 24V, IP67, 3000K
Article nr.: 86550-V2

TECHNICAL DATA

Power	90 W
Psb	0,00 W
Current mA	3.750 mA
Voltage	24 V
Amount of LED	1500
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_E
CRI	≥ 80
Lifetime L70B50	50.000 h
Lifetime L90B10	33.000 h
Suitable light source	





**VARDaflex Standard IP67 Reach25
Flex.LED Strip, 24V, IP67, 3000K**
Article nr.: 86550-V2

TECHNICAL DRAWING

