




VARDaflex Standard IP67 Reach25 Flex.LED Strip, 24V, IP67, 3000K

Article nr.: 86550

flexible LED-strip with self adhesive backside, · for indoor and outdoor use, IP67 · not uv-resistant · ·
can be separated every 100 mm or 6 LEDs · number of LEDs: 1500 · LED pitch: 16.67 mm · beam
angle: 120° · CRI: >80 · luminous flux per meter: 389 lm · input: 24V DC · power per meter: 4 W ·
lifetime L70B50: >= 67,000 h · energy efficiency class: F · LxWxH in mm: 25,000 x 12 x 6 · · Maximum
length per connection: 25 meter. New connectors for greater length. · Delivery contents: 5 meter reel
with 150 mm connecting cable, · 100 x mounting bracket made from silicone, 4 x in-feeder cap, · 4x
end cap

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094865508
Length	25000.00 mm
Width	12.00 mm
Height	6.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	9725.00 lm
Lightoutput per LED	6.48 lm
Lamp	including LED
IP rating	67






**VARDaflex Standard IP67 Reach25
Flex.LED Strip, 24V, IP67, 3000K**
Article nr.: 86550

TECHNICAL DATA

Power	100 W
Psb	0,00 W
Current mA	4.167 mA
Voltage	24 V
Amount of LED	1500
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	67.000 h
Lifetime L90B10	35.000 h
Suitable light source	

CE

RoHS





**VARDaflex Standard IP67 Reach25
Flex.LED Strip, 24V, IP67, 3000K**
Article nr.: 86550

TECHNICAL DRAWING

