




VARDAflex 4inONE-60 - 5M-Ro. Flex. LED Leiste, Innen, RGBWW 3000K

Article nr.: 79543

flexible LED Strip with self adhesive backside, · for indoor use. · Can be separated every 100 mm or 6 LEDs · Number of LEDs: 300 · LED pitch: 16.67 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 1080 lm · luminous flux 3000K per meter: 557 lm · Voltage: 24V DC · Power per meter: 19.2 W · Lifetime L70B50: >= 36.000 h · energy efficiency class: F · LxWxH in mm: 5.000 x 12 x 2 · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Easy installation with solderless connector (optional). · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter roll

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094795430
Housing colour	Weiss
Length	5000.00 mm
Width	12.00 mm
Height	2.00 mm
LED colour	RGBW 3000K
Lightoutput per fixture	5400.00 lm
Lightoutput per LED	18.00 lm
Lamp	including LED





VARDAflex 4inONE-60 - 5M-Ro. Flex. LED Leiste, Innen, RGBWW 3000K

Article nr.: 79543

TECHNICAL DATA

IP rating	20
Power	96 W
Current mA	4.000 mA
Voltage	24 V
Amount of LED	300
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	36.000 h
Lifetime L90B10	33.000 h
Suitable light source	





VARDAflex 4inONE-60 - 5M-Ro. Flex.
LED Leiste, Innen, RGBWW 3000K
Article nr.: 79543

TECHNICAL DRAWING

