




VARDAflex 4inONE-72 - 5M-Ro. Flex. LED Leiste, Innen, RGBNW 4000K

Article nr.: 79554

for indoor use, IP20 · Can be separated every 83.33 mm or 6 LEDs · Number of LEDs: 360 · LED pitch: 13.89 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 1032 lm · luminous flux 4000K per meter: 516 lm · Voltage: 24 V DC · Power per meter: 19,2 W · Lifetime L70B50: ≥ 36.000 h · energy efficiency class: F · LxWxH in mm: 5.000 x 12 x 2.2 · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Easy installation with solderless connector (optional). · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter reel

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094795546
Housing colour	ohne
Length	5000.00 mm
Width	12.00 mm
Height	2.20 mm
LED colour	RGBW 4000K
Lightoutput per fixture	5160.00 lm
Lightoutput per LED	14.33 lm
Lamp	including LED






VARDAflex 4inONE-72 - 5M-Ro. Flex. LED Leiste, Innen, RGBNW 4000K

Article nr.: 79554

TECHNICAL DATA

IP rating	20
Power	96 W
Current mA	4.000 mA
Voltage	24 V
Amount of LED	360
Temperature range	-20 - 45
LED per meter	72
Dimension of segments	83.33 mm
Energy efficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	36.000 h
Lifetime L90B10	33.000 h
Suitable light source	





VARDAflex 4inONE-72 - 5M-Ro. Flex.
LED Leiste, Innen, RGBNW 4000K
Article nr.: 79554

TECHNICAL DRAWING

