




VARDAflex 4inONE-84 - 5M-Ro. Flex. LED Leiste, Innen, RGBWW 3000K

Article nr.: 79563

flexible LED Strip with self adhesive backside, · for indoor use. · Can be separated every 7.1 cm or 6 LEDs · Number of LEDs: 420 · LED pitch: 11.91 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 1198 lm · luminous flux 3000K per meter: 672 lm · Voltage: 24V DC · Power per meter: 27 W · Lifetime L70B50: >= 36.000 h · energy efficiency class: F · LxWxH in mm: 5.000 x 12 x 2 · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Easy installation with solderless connector (optional). · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter roll

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094795638
Housing colour	Weiss
Length	5000.00 mm
Width	12.00 mm
Height	2.00 mm
LED colour	RGBW 3000K
Lightoutput per fixture	5990.00 lm
Lightoutput per LED	14.26 lm
Lamp	including LED






VARDAflex 4inONE-84 - 5M-Ro. Flex. LED Leiste, Innen, RGBWW 3000K

Article nr.: 79563

TECHNICAL DATA

IP rating	20
Power	135 W
Current mA	5.625 mA
Amount of LED	420
Input voltage	24
Temperature range	-20 - 45
LED per meter	84
Dimension of segments	71.00 mm
Energy efficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	36.000 h
Lifetime L90B10	33.000 h
Suitable light source	





VARDAflex 4inONE-84 - 5M-Ro. Flex.
LED Leiste, Innen, RGBWW 3000K
Article nr.: 79563

TECHNICAL DRAWING

