




VARDAflex Single Select 19W 5M-R.
Flex.LEDStrip, 24V, Innen, 2700-6300K
 Article nr.: 84859-V2

flexible LED Strip with self adhesive backside, · for indoor use IP20 · · can be separated every 8.33 mm or each LED · number of LEDs: 600 · LED pitch: 8.33 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 2129 lm · voltage: 24V DC · power per meter: 19 W · lifetime L70B50: >= 50,000 h · LxWxH in mm: 5,000 x 10 x 1.3 · · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Easy installation with solderless connector (optional). · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter roll with 300 mm connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094818597
Housing colour	Weiss
Length	5000.00 mm
Width	10.00 mm
Height	1.30 mm
LED colour	2700-6300K tunable white
Lightoutput per fixture	10645.00 lm
Lightoutput per LED	17.74 lm
Lamp	including LED





VARDAflex Single Select 19W 5M-R.
Flex.LEDStrip, 24V, Innen, 2700-6300K
 Article nr.: 84859-V2

TECHNICAL DATA

IP rating	20
Power	95 W
Psb	0,00 W
Current mA	3.958 mA
Voltage	24 V
Amount of LED	600
Temperature range	-10 - 55
LED per meter	120
Dimension of segments	8.33 mm
Energy efficiency class	EEK-Label_E
CRI	≥ 80
Lifetime L70B50	50.000 h
Suitable light source	





VARDAflex Single Select 19W 5M-R.
Flex.LEDStrip, 24V, Innen, 2700-6300K
Article nr.: 84859-V2

TECHNICAL DRAWING

